



Link-Belt RTC-8065 Series II

65 UST (60 MT) ROUGH TERRAIN CRANE

- 38 - 115 ft (11.6 - 35.0 m) 4-section full power boom
- Optional 35 - 58ft (10.7 - 17.7 m) two-piece offsettable fly
- Optional two 16 ft (4.88 m) extensions plus 58 ft (17.7 m) two-piece bi-fold lattice fly
- 211 ft 7 in (64.5 m) maximum tip height
- Height: 12 ft 2 in (3.7 m);
Width: 10 ft 7 in (3.2 m)
Length: 45 ft 6 in (13.9 m)
- 23.7 mph (38.1 km/hr) travel speed
- 14 ft 7 in (4.45 m) wheel base
- 26.5x25 tires
- Spicer 6 speed power shift transmission
- 24 ft (7.32 m) outrigger spread
24 ft (7.32 m) outrigger base
- 16,883 lbs (7 658kg) maximum winch line pull
- 459 fpm (139.9 m/min) maximum winch line speed

KEY FEATURES:

- Fully rigged transport weight of less than 90,000 lbs (40 832.3 kg)
- Boom wear pads have Teflon pucks that lubricate the boom sections (no grease)
- Four fly options feature four offset positions of 2°, 15°, 30°, and 45°
- Next generation operator's cab with improved visibility and ergonomics
- Integral air conditioning - optional
- 4-Link suspension on the rear axle with an optional Hydro-Gas Ride™ system
- 4-mode steering controlled from the steering wheel
- Full-length flat deck with integrated steps and handholds
- Large swing out engine hood doors for ease of service
- Access ladders and folding guardrails

| [PRINT THIS PAGE](#) |

© Copyright 2011 Link-Belt Construction Equipment Company, Lexington, Kentucky